

Pulverizer FU 950/1050



High performance special tool for pulverizing

With 360° endless hydraulic rotation or fixed

Oil supply for rotation unit by integrated couplers of the A-Lock

Exchangeable, turnable cutting edge for reinforcement steel

Jaw enforced with surface layer welding

Made with special wear steel

Special rapid-action valve for faster movements



ATTENTION: the hydraulic values indicated here after are not to be considered for the regulation of the excavator – please use the instructions!

Model	FU 950	FU 1050
Max. opening, mm	950	1050
Depth of bite, mm	850	890
Jaw width, mm	540	600
Hydraulic data		
Max. breaking force at 350 bar, to	131	175
Breaker Open / close	max. 350 bar / max. 240 l/min	max. 350 bar / max. 275 l/min
Time for open / close, sec	3,28 / 1,23	5,56 / 2,63
Time with "Speed up"-valve, sec	1,54 / 1,23	2,02 / 2,63
Breaker rotation	max 200 bar @ 20-25 l/min	max 200 bar @ 20-25 l/min
Data of cutting edge		
Opening in the middle of the edge, mm	307	330
Length of cutting edge (incision system), mm	160	175
Cutting force (middle of the edge), to	202	284
Weight		
Turnable models / Excavator weight	2.010 kg > 20 to	2.800 kg > 30 to
Fixed models / Excavator weight	1.750 kg > 18 to	2.500 kg > 28 to



WIMMER Hartstahl GmbH & Co KG and WIMMER Felstechnik GmbH
 Industriestraße 3, A-5303 Thalgau, AUSTRIA, Tel. +43 (0)6235 6655-0, Fax DW-18

WIMMER International CZ s.r.o., Rudolfovska 170 a, 370 01 České Budějovice,
 Tel. +420 387 203 735, Fax +420 387 203 736

office@wimmer.info

www.wimmer.info



Authorized WIMMER Dealer: